

ArbTrak 200

Go anywhere traction that's right for the big boys!

GreenMech
The Professionals' Choice



Customer category

Contractor • Large Scale Forestry Clearance

High performance, excellent ground clearance and decisive traction all reflect the capabilities of the ArbTrak 200 in most high-volume clearance and recycling projects. Specified by major contractors on demanding projects in difficult terrains because its high performance track system gives excellent access to work sites instead of bringing materials to the chipper. Large feed hopper and in-feed dimensions will keep a team of handlers busy all day long without the need to trim branches to size. A true contractors machine!

The backbone of the ArbTrak 200s design is based on a deep beam, high tensile steel chassis which creates tremendous strength and ensures a robust performance. A new, generous in-feed hopper, measuring 1200mm x 840mm, means that free-flow of bulky material can be handled without having to trim to a more manageable size. As the material passes through twin, horizontal, hydraulically powered feed rollers, the patented electronically controlled No-Stress system automatically manages the throughput of material to maximise chipping efficiency.

Key features

- ⊙ 200mm chipping capacity
- ⊙ 45hp Kubota turbo diesel engine
- ⊙ Disc-Blade chipping technology
- ⊙ Bottom-bar Safety Mechanism
- ⊙ No-Stress power control
- ⊙ Twin horizontal, hydraulic feed rollers
- ⊙ High speed track system
- ⊙ 1600kg weight



Capacity	200mm
Engine Make	Kubota
Engine	45hp
Fuel	Diesel
Tractor Required	n/a
Chipping Flywheel	Disc Type
Flywheel Speed	1500rpm
Blades	4
Hydraulic Feed Rollers	Twin Horizontal Hydraulic
Turntable	n/a
Power Control	No-Stress
Fuel Capacity (engine)	31 L
Tyre Size (towed)	n/a
Spare Wheel	n/a

Tonnes per hour	7
Infeed Chute Aperture	1200mm x 840mm
Infeed Throat Size	200mm x 280mm
Discharge Chute	280° Rotation
Hydraulic Oil Capacity	42 L
Clutch	Yes
Hour Meter	On RDS control box
Length (transport)	3230mm
Width (transport)	1410mm
Height	2612mm
Weight	1600kg
Sound Power LWA	116dB(A)
Sound Pressure LPA	92dB(A)
Bottom-bar Safety Mechanism	Standard